

DRY BLOCK CALIBRATOR FXP-1

Temperature bath for the calibration of winding & oil temperature indicators



BENEFITS OF FXP 1

- ❑ IMPROVED OPERATOR SAFETY
- ❑ NO HOT OIL TO SPILL
- ❑ ENVIRONMENTALLY FRIENDLY DESIGN
- ❑ SAFE TO TOUCH
- ❑ EASE OF USE WITH PT 100 INTERFACE
- ❑ CALIBRATION EFFICIENCY AND ACCURACY FAR GREATER THAN OIL INSTRUMENTS
- ❑ FULLY PORTABLE
- ❑ SIZE & NUMBER OF WELLS TO YOUR REQUIREMENTS
- ❑ TEXTURED POWDER COATING FINISH
- ❑ SPARES READILY AVAILABLE
- ❑ ONE YEAR GUARANTEE
- ❑ UNITS MANUFACTURED IN RSA

SPECIFICATIONS

- Voltage Rating (50 Hz): 230 V
- Fuse Rating: 2 A
- Power consumption: 400 W
- Dimensions: 350 x 250 x 200 mm
- Weight: 12 kg
- Maximum Temperature: 150 °C
- Numbers of bores: 4 x 18 mm
- Thermometer Pocket: 1 x 9 mm
- Depth of Bores: 170 mm
- Control & Resolution: PID (0.1 °C)
- Uncalibrated Accuracy: ± 2 °C
- Stability: ± 0.5 °C
- Separate read-out: No